



d3 é o diâmetro do anel não tensionado.

Os anéis do grupo 503 são fornecidos facultativamente numa das formas acima.

Código Stamper para encomenda	ANEL								RANHURA			DADOS COMPLEMENTARES			
	d3 max.	d1 min.	d1 máx..	e	d4	Peso Kg/1000	d2	Tol.	m	d4 mont.	n min	Pn (Kgf) min.	Pn (Kgf) máx.	g máx.	n.adm. (RPM)
00.503.012	1,2	1,4	2,0	0,3	2,90	0,009	1,2	0 -0,06	0,34	3,0	0,6	2,0	10,0	0,4	47.000
00.503.015	1,5	2,0	2,5	0,4	3,90	0,021	1,5	0 -0,06	0,44	4,0	0,8	6,8	15,7	0,6	42.000
00.503.019	1,9	2,5	3,0	0,5	4,40	0,040	1,9	0 -0,06	0,54	4,5	1,0	10,5	20,7	0,7	40.000
00.503.023	2,3	3,0	4,0	0,6	5,90	0,069	2,3	0 -0,06	0,64	6,0	1,0	14,6	42,0	0,9	38.000
00.503.032	3,2	4,0	5,0	0,6	6,90	0,088	3,2	0 -0,75	0,64	7,0	1,0	22,7	58,0	0,9	35.000
00.503.040	4,0	5,0	7,0	0,7	8,85	0,158	4,0	0 -0,75	0,74	9,0	1,2	35,3	95,0	1,0	32.000
00.503.050	5,0	6,0	8,0	0,7	10,85	0,236	5,0	0 -0,75	0,74	11,0	1,2	43,0	115,0	1,0	28.000
00.503.060	6,0	7,0	9,0	0,7	11,80	0,255	6,0	0 -0,75	0,74	12,0	1,2	51,0	135,0	1,1	25.000
00.503.070	7,0	8,0	11,0	0,9	13,80	0,474	7,0	0 -0,09	0,94	14,0	1,5	59,0	200,0	1,3	22.000
00.503.080	8,0	9,0	12,0	1,0	15,75	0,660	8,0	0 -0,09	1,05	16,0	1,8	66,8	250,0	1,5	20.000
00.503.090	9,0	10,0	14,0	1,1	18,20	1,000	9,0	0 -0,11	1,15	18,5	2,0	75,0	300,0	1,6	17.000
00.503.100	10,0	11,0	15,0	1,2	19,70	1,120	10,0	0 -0,11	1,25	20,0	2,0	82,0	350,0	1,8	15.000
00.503.120	12,0	13,0	18,0	1,3	22,70	1,770	12,0	0 -0,11	1,35	23,0	2,5	98,0	465,0	1,9	13.000
00.503.150	15,0	16,0	24,0	1,5	28,70	3,370	15,0	0 -0,13	1,55	29,0	3,0	122,0	660,0	2,2	11.000
00.503.190	19,0	20,0	31,0	1,75	36,70	6,420	19,0	0 -0,13	1,80	37,2	3,5	157,0	845,0	2,5	7.600

Reservamo-nos ao direito de modificação das dimensões acima sem consulta prévia.